



Embossed Wearlayer with PU finishing

Design Film

Comfort layer

**No installation limits and no joints required.**  
Dryback solution that will guarantee a long-term durability of your floor.

TEST	STANDARD
Dimensions	EN 427 / EN 428
Emboss / Surface	
Impact Sound Reduction	EN 140
Use Classification	EN 16511
Weight	EN 430
Fire Performance	EN 13501
Abrasion Wear	EN 425
Dimensional Stability	EM 434
Indentation	EN 433
Chemical Resistance	EN 423
Anti-static Resistance	EM 1815
Slippery Resistance	DIN 51133 EN 13893
Underfloor Heating	
Thermal Resistance	EN 12524
Thermal Conductivity	EN 12667
Toxicity	EN 71
Emissions Value AgBB/Dibt low VOC (U-Sign)	
Resistance to Fading	ISO 105 B02 2014-09

LUNGO COLLECTION	METROPOLITAN COLLECTION	SCANDINAVIAN COLLECTION
1829 x 229 x 2,5 mm	1219 x 229 x 2,5 mm	1219 x 229 x 2,5 mm
Registered Wood / Regular Wood* Semi-matte	Regular Wood Semi-matte	Regular Wood Semi-matte
5 dB	5 dB	5 dB
42	42	42
4,5 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>	3,6 kg/m <sup>2</sup>
Bfl - S1		
Pass Castor Chair (W)		
Approved		
max 0,08mm		
Class 0 - Good		
< 2kV		
Class R9 Class DS		
Approved 27°C		
0,036 m2 K/W		
10.076 w(m-K)		
Non Toxic		
Certified		
6/8 Good		

\* Registered Wood: products 9550 and 9551 / Regular Wood: products 9701, 9736 and 9737

